PTFE трубки (тефлон)

	внутренний диаметр（ID）	Внешний диаметр（OD）			метров в 1 катушке
Стандарт AWG		S	T	L	
30	0,3	0,76	0,76	0,6	305
28	0,38	0,84	0,84	0,68	305
26	0,46	0,92	0,92	0,76	305
24	0,56	1,16	1,06	0,86	305
23	0,66	1,26	1,16	0,96	305
22	0,71	1,31	1,21	1,01	305
21	0,81	1,41	1,31	1,11	305
20	0,86	1,66	1,46	1,16	305
19	0,96	1,76	1,56	1,26	305
18	1,07	1,87	1,67	1,37	305
17	1,19	1,99	1,79	1,49	305
16	1,34	2,14	1,94	1,64	305
15	1,5	2,3	2,1	1,8	153
14	1,68	2,48	2,28	2,08	153
13	1,93	2,73	2,53	2,33	153
12	2,16	2,96	2,77	2,56	153
11	2,41	3,21	3,01	2,81	153
10	2,69	3,49	3,29	3,09	153
9	3	4	3,76	3,4	100
8	3,38	4,38	4,14	3,78	100
7	3,76	4,76	4,52	4,16	100
6	4,22	5,22	4,98	4,72	100
5	4,72	5,72	5,48	5,22	100
4	5,28	6,28	6,04	5,78	100
3	5,94	6,94	6,7	6,44	100
2	6,68	7,68	7,44	7,18	100
1	7,46	8,46	8,22	7,96	100
0	8,38	9,38	9,14	8,88	100

AWG 16-30 305метров на катушке, AWG10-15 - 153м, AWG 0-9 - 100м

Толщина стенки и пробивное напряжение

L type 150V rating.	T type 300V rating.	S type 600V rating.	HOSE TUBE 800V rating.
Minimum thickness at any point of the wall _mm	Minimum thickness at any point of the wall _mm	Minimum thickness at any point of the wall _mm	Minimum thickness at any point of the wall _mm
30L-15L : 0.114 14L-9L : 0.165 8L-7L : 0.179 6L-0L : 0.203	30T-10T : 0.229 9T-0T : 0.279	30S-26S : 0.229 24S-19S : 0.305 18S-10S : 0.406 9S-0S : 0.483	HOSE 3*4 :0.5 HOSE 4*6 :1.0