


COIL FORMER


General data 10-pins EFD25/13/9 coil former

PARAMETER	SPECIFICATION
Coil former material	phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E41429
Pin material	copper-tin alloy (CuSn), tin (Sn) plated
Maximum operating temperature	180°C, "IEC 60085", class H
Resistance to soldering heat	"IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s
Soldeerability	"IEC 60068-2-20", Part 2, Test Ta, method 1,235°C,2s









Winding data and area product for 10-pins EFD25/13/9 coil former

NUMBER OF SECTIONS	WINDING AREA (mm²)	MINIMUM WINDING WIDTH (mm)	AVERAGE LENGTH OF TURN (mm)	AREA PRODUCT Ae x Aw (mm ⁴)	TYPE NUMBER
1	42	16.70	50	2390	EFD-2501-1S-10P

Tolerances unless otherwise specified: $0 < L \le 4 \pm 0.10$ $4 < L \le 16 \pm 0.20$ $16 < L \le 45 \pm 0.30$ $45 \le L \pm 0.40$ Pin Dim: ± 0.05 Thickness: ± 0.20 Pin Pitch: ± 0.20

Dimensions: (mm)	REMARK			
	(11111)	Mould No.	: EFD2501	Bobbin material: PM9820
		Code No.:	FAY01091	Available for Fuan core: EFD25/13/9
		•		



Fuan Electronics

TEL :0086-514-87693589 EML :sales@fuantronics.net WEB:www.fuantronics.net

Make: P.Xiao	Material Number: A4H250100100	
Checked: Beson. zhan	Document/Rev: 00	
Approved: Anson. zhan	Date of Recognition: Oct./17/2019	